

BIM STRUCTURED DATA SHEET REF 6

Structured Data_isofast_IF2-6,1_Nov-17_GB_v1

Title Block	Template Category	Self Drilling, self tapping fastener Fasteners - FR		
itle Block	Category Description	Fasteners suitable for self drilling and threadforming in Flat Roof applications		
itle Block	Template Version	1		
nio Bioon	Tomplate Vereien	'		
		For fastening insulation and single ply membrane to steel, con		
itle Block	Suitability of Use	applications and used in conjunction with stress plates. Their u	use comprise	s connections with predominatly static loads.
itle Block	Parameter Name/ Question	Value/ Answer	Units	Notes
Manufacturers Data	Manufacturer	SFS intec Ltd	Text	Hotes
flanufacturers Data	Manufacturer Website	www.sfsintec.co.uk	URL	
Manufacturers Data	Product Range	isofast	Text	
Manufacturers Data	Fastener Product Name	IF2-6,1	Text	
Manufacturers Data	Thermally Broken Insulation Sleeve Product Name	N/A	Text	
Manufacturers Data	Thermally Broken Membrane Sleeve Product Name	N/A	Text	
Manufacturers Data	Insulation Stress Plate Name	ID-70x70 or IF3-S	Text	
Manufacturers Data	Membrane Stress Plate Name	IRD-82x40	Text	
Manufacturers Data	Product Literature	SFS intec catalogue	URL	
Manufacturers Data	Features	For the fastening of insulation or single ply membrane to steel, Concrete	Text	
wandlacturers Data	i catales	and Plywood / OSB3 decks.	TOX	
Manufacturers Data	ISO 9001	www.sfsintec.co.uk/quallity_management	URL	
Manufacturers Data	CE Mark	Yes	Text	
Manufacturers Data	FM Approval	Yes	Text	Known to FM as Dekfast #14
Manufacturers Data	SINTEF Approval	No	Text	Tallotti to Fin do Bondot // 14
	Touris Tippiovai	li io	TOAL	
Application Data	Flat, Mono Pitch, Duopitch or Barrell roof	Flat, Mono Pitch, Duopitch or Barrell	Text	
Application Data	System Type	Flat Roof membrane & Insulation attachment	Text	
Application Data	Membrane attachment type	For fixing in rows at Membrane seams	TOAL	
Application Data	Deck type	Steel deck, mimimum 0.63mm, Concrete (min C12/15, 60mm),	Text	Pullout testing by SFS intec is required - For all Concrete
tppiloation bata	Dook type	Plywood / OSB3 (Min 18mm)	TOAL	& refurbished decks
Application Data	Environmental Corrosion Category to BS EN12944	C1	Text	a fordibioned decide
Application Data	Estimated Service Life C1 (BS ISO 15686-1:2011)	20	Up to Years	
Application Data	Warranty C1	10	Years	
Application Data	Twantanty or	110	Toars	
Dimensional Data	Fastener Thread Diameter	6,1	mm	
Dimensional Data	Fastener Head Diameter	0,1	mm	
Dimensional Data	Fastener Drive Position	External	Text	
Dimensional Data	Fastener Head Style	PH3	Text	
Dimensional Data	T dotterior riodd Otyle	32, 52, 76, 102, 127, 152, 178, 203, 254, 305	mm	
Diricisional Data	'	02, 02, 10, 102, 121, 102, 110, 200, 204, 000	111111	
Dimensional Data	Effective Fastener Thread Length	100	mm	
Dimensional Data	Fastener Drilling Capacity - Aluminium	N/A	mm	
Dimensional Data	Fastener Drilling Capacity - Steel	2x1.25	mm	
Dimensional Data	Thermally Broken Insulation Sleeve washer dimension	N/A	mm	
Dimensional Data	Thermally Broken Insulation Sleeve Lengths	N/A	mm	
Dimensional Data	Thermally Broken Membrane Sleeve washer dimension	N/A	mm	
Dimensional Data	Thermally Broken Membrane Sleeve Lengths	N/A	mm	
Dimensional Data	Insulation Stress Plate Dimension	ID: 70x70, IF3-S: 75mm dia	mm	
Dimensional Data	Membrane Stress Plate Dimension	82x40	mm	
onordia Data				<u></u>
echnical Data	European Technical Approval (ETA)	ETA-08/0262	URL	Pullout testing by SFS intec is required - Concrete & refurb decks.
Fechnical Data	Declaration of Performance (DoP)	<u> </u>	URL	. and a country by or o intoo to required - obtribute a retail backs.
Fechnical Data	Fastener Surface Coating	Durocoat	Text	
Technical Data	Fastener Material	Carbon Steel	Text	
Technical Data	Fastener Material Grade	N/A	Text	
echnical Data	Fastener Material Grade to EN standard	N/A	Text	
echnical Data	Minimum Fastener Embedment into Steel Deck	20	URL	
echnical Data	Minimum Fasterier Embedment into Steel Deck Minimum Fasterier Embedment into Timber / OSB3 Deck	30	URL	
echnical Data	Minimum Fastener Embedment into Concrete Deck	25	mm	
echnical Data	Thermally Broken Insulation / membrane Sleeve material	N/A	Text	
echnical Data	Insulation / Membrane Stress plate Material Grade	Carbon Steel	Text	
Comilicai Data	prisulation / Michibiane Otress plate Material Oface	Daibon Otool	I CAL	<u></u>
Classification Data	Uniclass 2015	Pr 20 29 76 76	Text	
Classification Data	Uniclass 2015 Description	Self-drilling sheet metal screws	Text	
nassincation Data	Officials 2010 Description	Joen-drining oricet frictal ociews	TEXT	<u></u>
Sustainability Data	Country of Manufacture	Turkey	Text	
Justali iability Data			URL	
Sustainability Data	Environmental Product Declaration	No Performance Declared		