

## **BIM STRUCTURED DATA SHEET REF 10**

Structured Data\_isofast\_TPR-L\_Nov-17\_GB\_v1

Title Block	Template Category	TPR-L Peel Rivets - FR		
Title Block	Category Description	Peel Rivet Fasteners suitable for use in Flat Roof applications		
		Peel Rivet Pasteners suitable for use in Flat Roof applications		
Title Block	Template Version	1		
		For fastening insulation and single ply membrane to critical decks. These connections are for external applications and used in		
itle Block	Suitability of Use	conjunction with stress plates. Their use comprises connection		
Title Block		Value/ Answer		
	Parameter Name/ Question		Units	Notes
lanufacturers Data	Manufacturer	SFS intec Ltd	Text	
lanufacturers Data	Manufacturer Website	www.sfsintec.co.uk	URL	
lanufacturers Data	Product Range	isofast	Text	
lanufacturers Data	Fastener Product Name	TPR-L-6,3	Text	
lanufacturers Data	Thermally Broken Insulation Sleeve Product Name	N/A	Text	
anufacturers Data	Thermally Broken Membrane Sleeve Product Name	N/A	Text	
lanufacturers Data	Insulation Stress Plate Name	ID-70x70	Text	IDD 70 70 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
anufacturers Data	Membrane Stress Plate Name	IRD-70x70 or IF/IG-C-70x70	Text	IRD-70x70 when used with insulation. IF/IG-C with flat surfaces
anufacturers Data	Product Literature	SFS intec catalogue	URL	
anufacturers Data	Features		Text	See Application Data
	100 0004	For the fastening of insulation or single ply membrane to critical decks*.		
anufacturers Data	ISO 9001	www.sfsintec.co.uk/quallity_management	URL	
anufacturers Data	CE Mark	Yes	Text	
anufacturers Data	FM Approval	No	Text	
lanufacturers Data	SINTEF Approval	Yes	Text	
		<u> </u>		
pplication Data	Flat, Mono Pitch, Duopitch or Barrell roof	Flat, Mono Pitch, Duopitch or Barrell	Text	
pplication Data	System Type	Flat Roof membrane & Insulation attachment	Text	
pplication Data	Membrane attachment type	For fixing in rows at Membrane seams		
pplication Data	Deck type	Woodwool, steel <0,63mm thick or aluminium	Text	
pplication Data	Environmental Corrosion Category to BS EN12944	C3	Text	
pplication Data	Estimated Service Life C3 (BS ISO 15686-1:2011)	30	Up to Years	
pplication Data	Warranty C1	25	Years	
imensional Data	Fastener Thread Diameter	6,3	mm	
imensional Data	Fastener Head Diameter	12,5	mm	
imensional Data	Fastener Drive Position	N/A	Text	
imensional Data	Fastener Head Style	N/A	Text	
imensional Data	Fastener Length	38, 51, 64, 76, 88, 102, 127, 152, 178, 203, 229, 254	mm	
imensional Data	Effective Fastener Thread Length	N/A	mm	
Dimensional Data	Fastener Drilling Capacity - Aluminium	N/A	mm	
imensional Data	Fastener Drilling Capacity - Steel	N/A	mm	
imensional Data	Thermally Broken Insulation Sleeve washer dimension	N/A	mm	
imensional Data	Thermally Broken Insulation Sleeve Lengths	N/A	mm	
imensional Data	Thermally Broken Membrane Sleeve washer dimension	N/A	mm	
imensional Data	Thermally Broken Membrane Sleeve Lengths	N/A	mm	
imensional Data	Insulation Stress Plate Dimension	70x70	mm	
imensional Data	Membrane Stress Plate Dimension	82x40	mm	
echnical Data	European Technical Approval (ETA)	ETA-08/0262	URL	
echnical Data	Declaration of Performance (DoP)		URL	
echnical Data	Fastener Surface Coating	N/A	Text	
echnical Data	Fastener Material	Aluminium	Text	
echnical Data	Fastener Material Grade	N/A	Text	
echnical Data	Fastener Material Grade to EN standard	N/A	Text	
echnical Data	Minimum Fastener Embedment into Steel Deck	SFS intec catalogue	URL	
echnical Data	Minimum Fastener Embedment into Timber / OSB3 Deck	SFS intec catalogue	URL	
echnical Data	Minimum Fastener Embedment into Concrete Deck	N/A	mm	
echnical Data	Thermally Broken Insulation / membrane Sleeve material	N/A	Text	
echnical Data	Insulation / Membrane Stress plate Material Grade	Carbon Steel	Text	
				· -
lassification Data	Uniclass 2015	Pr_20_29_76_76	Text	
lassification Data	Uniclass 2015 Description	Self-drilling sheet metal screws	Text	
The state of the s				
ustainability Data	Country of Manufacture	Germany	Text	
	Environmental Product Declaration	No Performance Declared	URL	
ustainability Data				

The details stated are results of tests and/or calculations and therefore are non-binding and do not represent guaranties or warranted characteristics for none-specified applications. All calculations therefore have to be checked and approved by the responsible planner ahead of execution. The user is responsible to assure compliance with all applicable laws and regulations.