

BIM STRUCTURED DATA SHEET

Structured Data_SXC5-6,3_Apr-19_GB_v1

Title Block	Template Category	Self Drilling Fasteners - RC
Title Block	Category Description	Fasteners suitable for self drilling, threadforming and sealing in roof and wall cladding applications
Title Block	Template Version	2
		For fastening steel sheeting or steel lined composite panels to steel/ timber substructures. These connections can be internal or external
Title Block	Suitability of Use	applications and their use comprises connections with predominatly static loads.

ILIE BIOCK	Suitability of Use	applications and their use comprises connections with predomin	ally static loc	aus.
Title Block	Parameter Name/ Question	Value/ Answer	Units	Notes
anufacturers Data	Manufacturer	SFS intec Ltd	Text	
anufacturers Data	Manufacturer Website	www.sfsintec.co.uk	URL	
anufacturers Data	Product Range	SXC5	Text	
lanufacturers Data	Product Model Number	No Performance Declared	Text	Values cover complete product range
lanufacturers Data	Product Literature	SXC5-6.3 Literature	URL	
idiraraotaroro Bata		Composite panel fastener with thread free zone for effective sealing and	0.12	
Manufacturers Data	Features	sheet support	Text	
Ianufacturers Data	ISO 9001	www.sfsintec.co.uk/quallity_management	URL	
lanufacturers Data	CE Mark	Yes	Text	
arrandotaroro Bata		1.00	1 0/1	•
pplication Data	Roof or Wall Coverings	Roof and Wall	Text	
oplication Data	System Type	Composite	Text	
pplication Data	Sub structure material	Steel - cold rolled, Aluminium	Text	
oplication Data	Environmental Corrosion Category to BS EN12944	C1,C2,C3,C4,C5,C5i	Text	
pplication Data	Estimated Service Life C3 (BS ISO 15686-1:2011)	50	Up to Years	
pplication Data	Warranty C3	40	Years	
imensional Data	Thread Diameter	6.3	mm	
imensional Data	Drive Position	External	Text	
imensional Data	Head Style	Hex 8mm, Low Profile Irius 12mm	Text	
imensional Data	Length	80, 100, 120, 140, 160, 190, 220, 250, 290, 345	mm	
imensional Data	Washer Dimension	16.19.29	mm	
imensional Data	Effective Thread Length	33-318	mm	
imensional Data	Drilling Capacity - Aluminium	2.0 - 5.0	mm	
imensional Data	Drilling Capacity - Steel	1.2 - 5.0	mm	
imensional Data	Product Weight per 100	1.225 to 5.240	kg	
echnical Data	Powder Coated Head/ Washer	Option	Text	Available to any RAL, BS or NCS colour
echnical Data	European Technical Approval (ETA)	ETA13/0183-2019	URL	
echnical Data	Declaration of Performance (DoP)	DoP - SXC5-6,3	URL	
echnical Data	Fastener Surface Coating	Zinc Flash	Text	
echnical Data	Fixing Material	Austenitic Stainless Steel - Bimetal	Text	
echnical Data	Fixing Material Grade	304/A2, 316/A4	Text	
echnical Data	Fixing Material Grade to EN standard	EN ISO 3506	Text	
echnical Data	Shear Performance (Qb)	10,639	Newtons	
echnical Data	Tensile Performance (Zb)	11,597	Newtons	
echnical Data	Free Spin Zone	Yes	Test	
echnical Data	Washer Material - Metal	Austenitic Stainless Steel	Text	
echnical Data	Washer Material Metal Grade	304/A2, 316/A4	Text	
echnical Data	Washer Material Metal Grade to EN standard	EN ISO 3506	Text	
echnical Data	Washer Material - Sealing	Vulcanised EPDM	Text	
Classification Data	Uniclass 2015	Pr_20_29_76_76	Text	
Classification Data	Uniclass 2015 Description	Self-drilling sheet metal screws	Text	
ustainability Data	Country of Manufacture	Turkey	Text	
Sustainability Data	Environmental Product Declaration	No Performance Declared	URL	

The details stated are results of tests and/or calculations and therefore are non-binding and do not represent guaranties or warranted characteristics for none-specified applications. All calculations therefore have to be checked and approved by the responsible planner ahead of execution. The user is responsible to assure compliance with all applicable laws and regulations.